

# B110CU

(For Flat Head Printers)

**RICOH**  
imagine. change.

## Thermal Transfer Ribbon Product Information

### RESIN SUPER SMEARLESS

Last update:  
Aug. 2016  
Ref: PS-1384 (Rev. 1)

#### RIBBON PROPERTY

- Base Material
- Base Thickness ( $\mu\text{m}$ )

Polyester film  
4.5  $\pm$  0.4

#### INK PROPERTY

- Ink Color

Black

#### IMAGE PROPERTY

- Image Density
- Image Resolution
- Scratch Resistance (scratched x 100 by sharp edge at 40°)
- Resistance to smear and heat (rubbed x 100 in 100°C)
- Chemical Resistance (wiped x 100 with cotton cloth at 100gf/cm<sup>2</sup>)
  - Ethanol, Methanol
  - IPA (Isopropyl Alcohol)
  - MEK (Methyl Ethyl Ketone)
  - Thinner
  - Xylene
  - Brake Fluid
  - Water

1.5 minimum  
Excellent  
Excellent  
Excellent  
Excellent  
Excellent  
Excellent  
Excellent  
Excellent  
Excellent

*\* All tests specifications are based on Ricoh's standard test results.*

#### USAGE ENVIRONMENT:

5 ~ 35°C (41 ~ 95°F), 30 ~ 85%RH

#### STORAGE CONDITIONS:

Keep indoors, away from high temperatures, high humidity and direct sunlight. Keep master rolls hanging horizontally.

#### GUARANTEE PERIOD:

- \*Finished rolls: 2 years after manufacturing
- \*Master rolls: 1 year after coating

#### FEATURES:

- Ideal for Automotive, Serial No. Plates, Circuit Board Labels and Pharmaceutical Applications
- Produces very high resolution even when printing using a 600dpi thermal head
- Excellent resistance to heat, chemicals, solvents and scratches
- UL recognized

*The above data represents product averages, allowing for industry accepted variances. These products should be tested in the end-use conditions to ensure that they meet the requirements of the specific application. Specifications may change without notice.*

RICOH ELECTRONICS, INC. DISCLAIMS ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE IN CONNECTION WITH THE CUSTOMER'S PURCHASE OF OUR PRODUCTS. IT IS CUSTOMER'S SOLE AND EXCLUSIVE RESPONSIBILITY TO TEST AND ENSURE SUITABILITY OF OUR PRODUCTS FOR ITS CUSTOMERS' OR END-USER'S APPLICATION.