



G25/G12: Wide Temperature Permanent Adhesive

- Excellent adhesion to a wide variety of surfaces including paper, wax paper bags, corrugated board, light waxed corrugated board, various packaging films, glass enamel, and polyethylene, as well as other plastic substrates.
- Specially designed for adhesion to cryovac film, even with light moisture condensation and to other low energy surfaces.
- Excellent initial tack.
- Strong self-dispensing performance in automatic printers.
- Complies with F.D.A. 175.105 for indirect food contact.

G8: Tight Removable Adhesive

- Good adhesion to most packaging substrates.
- Excellent removability from most substrates.
- Used for applications requiring clean removable properties, such as shelf tags, retail price labels, medical and industrial.
- Complies with F.D.A. 175.105 for indirect food contact.

G5: General Purpose Permanent Hot Melt Adhesive

- High initial contact.
- Excellent adhesion on packaging boxes, film and/or a wide range of substrates.
- Complies with F.D.A. 175.105 for indirect food contact.

G22: Permanent Hot Melt Adhesive for Moist Plastic Substrates at Low Temperatures

- High initial contact.
- Excellent adhesion on plastic substrates in high moisture environments such as meat and poultry processing.
- Complies with F.D.A. 175.105 for indirect food contact.

	Adhesives										
	Emulsion Acrylic					Hot Melt					
	G25/G12			G8		G5			G22		
Application Temperature	-40°F to 122°F (-40°C to 50°C)			10°F to 120°F (-12°C to 49°C)		35°F to 120°F (2°C to 49°C)			28°F to 122°F (-2°C to 50°C)		
Service Temperature	-65°F to 131°F (-54°C to 55°C)			-20°F to 120°F (-29°C to 49°C)		-40°F to 131°F (-40°C to 55°C)			-40°F to 122°F (-40°C to 50°C)		
Application Conditions	Applied at:			Applied at:		Applied at:			Applied at:		
	0°F / -18°C	35°F / 2°C	R.T.	10°F / -12°C	R.T.	0°F / -18°C	35°F / 2°C	R.T.	0°F / -18°C	35°F / 2°C	R.T.
PACKAGING FILMS	●●	●●	●●	●	●		●●	●●		●●	●●
PLASTIC	●●	●●	●●	●	●		●●	●●		●●	●●
CORRUGATED BOXES	●	●●	●●	●	●		●●	●●		●●	●●
PAPER	●●	●●	●●	●	●		●●	●●		●●	●●
METAL	●●	●●	●●	●	●		●	●●		●	●●
GLASS	●●	●●	●●	●	●		●●	●●		●●	●●
	Excellent - Test in actual application						●●				
	Fair - Test for suitability						●				
	NOT Recommended										

RICOH ELECTRONICS, INC. DISCLAIMS ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE IN CONNECTION WITH THE CUSTOMER'S PURCHASE OF OUR PRODUCTS. IT IS CUSTOMER'S SOLE AND EXCLUSIVE RESPONSIBILITY TO TEST AND ENSURE SUITABILITY OF OUR PRODUCTS FOR ITS CUSTOMERS' OR END-USER'S APPLICATION.

CONTACT INFORMATION

Copyright 2016 Ricoh Electronics, Inc.
 1125 Hurricane Shoals Rd.
 Lawrenceville, GA 30043
 All Rights Reserved

Company Info
 ISO14001 / ISO9001 Certified

Customer Service Department
 Toll-Free 1-800-843-7058
 Toll-Free Fax 1-888-873-7059
 Worldwide Fax +1-770-613-6478
 Email: orders@rei.ricoh.com