D110A

(For Flat Head & Near Edge Printers)

Thermal Transfer Ribbon Product Information

RESIN SPECIALTY (For Textile Applications)

RIBBON PROPERTY

- Base Material
- Base Thickness (µm)

INK PROPERTY

- Ink Color
- Ink Transparency

PRINTING PROPERTY

- Image Density Min. 0.8 (polyester) Min 1.0 (acetate)
- Image Resolution

IMAGE DURABILITY

- Ironing Resistance
- Smear Resistance (dry, wet)
- Washing Resistance (water)
- Washing Resistance (dry)
- Bleach Resistance

- Sweat Resistance

ID(GD): The differences in image (ground) density resulting from the "before test" and "after test" *All tests specifications are based on Ricoh's standard test methods.

USAGE ENVIRONMENT:	5 ~ 35ºC (41 ~ 95ºF), 30 ~ 85%RH
STORAGE CONDITIONS:	Keep indoors, away from high temperatures, high humidity and direct sunlight. Keep master rolls hanging horizontally.
GUARANTEE PERIOD:	
*Finished rolls:	4 years after coating

FEATURES:

- Printable on receiving cloths (nylon, polyester and acetate) and films
- Super smear resistance up to 150°C (302°F); no blurring of image occurs from ironing
- Print images are highly durable against water and dry cleaning
- Superior thermal head matching qualities using Ricoh's unique back-side coating

The above data represents product averages, allowing for industry accepted variances. These products should be tested in the enduse conditions to ensure that they meet the requirements of the specific application. Specifications may change without notice. RICOH ELECTRONICS, INC. DISCLAIMS ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE IN CONNECTION WITH THE CUSTOMER'S PURCHASE OF OUR PRODUCTS. IT IS CUSTOMER'S SOLE AND EXCLUSIVE RESPONSIBILITY TO TEST AND ENSURE SUITABILITY OF OUR PRODUCTS FOR ITS CUSTOMERS' OR END-USER'S APPLICATION.

Ricoh Electronics, Inc. • 1125 Hurricane Shoals Road • Lawrenceville, GA 30043 • www.RicohThermalProducts.com Customer Service: 1.800.843.7058 • Toll Free FAX: 1.888.843.7059 • email: orders@rei.ricoh.com

RICOH imagine. change.

Last update: Sep. 2022 Ref: PS-1794 (Rev. 3)

> Polyester film 4.5 ± 0.4

> > Blac More than 0.65 ~ 1.65

> > > Min. 1.2 (nylon)

Min. ANSI B

GD max. 0.07 (direct, covered with cloth) GD max. 0.07 (direct, covered with cloth) ID min 1.0 min. ANSI B (nylon) ID min 0.6 (polyester) ID min 0.7 (acetate) ID min 1.0 min. ANSI B (nylon) ID min 0.6 (polyester) ID min 0.7 (acetate) ID min 1.0 min. ANSI B (nylon) ID min 0.6 (polyester) ID min 0.8 (acetate) ID min 1.0 min. ANSI B (nylon) ID min 0.6 (polyester) ID min 0.8 (acetate)