



THERMAL TRANSFER RIBBONS

| GRADE | PRODUCT | PERFORMANCE CHARACTERISTICS | PRINTER |
|----------------------|---------|---|--------------------------|
| Wax-Resin | впоа | Designed to print on a wide variety of receiving materials including paper, coated paper and film at low and high printing speeds Highly resistant to chemicals and abrasion Minimizes static electricity and ink flaking while maximizing barcode scanning rates Suitable for a broad range of end-use applications | Flat Head |
| Resin | B125CS | General purpose resin ribbon designed to print on a wide variety of substrates including PP, PET, and coated paper Highly resistant to scratches, smears, and chemicals Superior image resolution and sensitivity Suitable for a broad range of end-use applications | Flat Head |
| | B110C | Engineered to print on film and synthetic materials Highly resistant to solvents (alcohol, petrol, kerosene, brake fluid, engine oil, car wax and more), heat, scratch, and smear Excellent print quality, exceptional sensitivity for high-speed printing Ideal for automotive and factory applications | Flat Head |
| | BIIOCR | Designed for film-based substrates, such as PET Unparalleled resistance to heat, abrasions, and solvents Outstanding resolution even when printing with a 600dpi thermal head Specifically produced for electronics, automotive, and medical applications | Flat Head |
| | B110CU | Designed for film-based substrates, such as PET Ultra-resistant to solvents (acetone, ethanol, toluene, MEX, xylene, thinner, and more), scratch, and smear Outstanding resolution even when printing with a 600dpi thermal head Ideal solution for healthcare, specimen, bioscience, and industrial applications | Flat Head |
| | B120EC | Universal resin ribbon designed to perform on a broad range of receiving materials, from paper to film, synthetic media such as PET, PVC, PE, and other coated papers Resistant to solvents (ethanol, kerosene, engine oil), and scratch Reliable, sharp-edge print quality that maximizes barcode scanning rates Ideal for applications where a high resistance to environmental conditions is required | Near Edge & Flat Head |
| | B120HS | Formulated for polyolefin labels such as PP and PE Outstanding resistance to oil, water, chemicals, scratch, and heat Excellent image quality, highly sensitive for high-speed printing Ideal for car battery applications | Flat Head |
| Resin for Textile | D110A | Designed to print on nylon, polyester, and acetate Produces a durable, smear-resistant image that withstands dry cleaning, water/stone/chemical washing, and ironing | Near Edge & Flat Head |
| | DIIOC | Formulated for textile printing on nylon, acetate, satin, and other materials Superior durability able to withstand washing, steam/dry cleaning, and ironing | Flat Head |