



PRODUCT OVERVIEW

DESCRIPTION

Ricoh's SYN-2 is a BOPP film-based synthetic label stock renowned for its durability and clarity, featuring a 2.4 mil caliper for optimal strength and flexibility. Engineered for high-quality printing and resistance to moistures and oils, SYN-2 offers a versatile labeling solution suitable for various industries and applications.

Features & Benefits

- Synthetic, film-based product with a semi-gloss finish
- Superior image performance under harsh weathering and high temperatures
- Increased flexibility for curved surface labeling while maintaining durability

SYN-2 SPECIFICATIONS

FACESTOCK PROPERTIES

ITEM	UNIT	SPECIFICATION	TEST METHOD
Basis Weight	lbs (24x36x500 sheets)	24.9± 1.0	ISO 4591
	g/m ²	40.5± 1.5	
Caliper	mil	2.4 ± 0.2	ISO 4591/4593
	µm	60.0 ± 3.0	
Tensile Strength	MD N/15mm	58 Minimum	DIN/ISO 527
	CD N/15mm	120 Minimum	
	MD mgf	108	TAPPI T543
	CD mgf	186	

LAMINATED PRODUCT

GRADE	UNIT	G12	
Application	°F	-40 to 122	Liner: 40 lbs Caliper: 2.5 mils ± 10% (64 ± 8 µm) Opacity: 65% Maximum (Photovolt)
Temperature	°C	-40 to 50	
Service	°F	-65 to 131	
Temperature	°C	-54 to 55	
Basis Weight (24 x 36 x 500)	lbs	84 ± 12	Adhesive Attributes: G12 – Wide temperature and permanent
	g/m ²	136 ± 19	
Caliper	µm	146 ± 19	
	mil	5.7 ± 0.7	

CERTIFICATES / REGULATIONS / DIRECTIVES

ISO9001 ISO14001

RICOH ELECTRONICS, INC. DISCLAIMS ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE IN CONNECTION WITH THE CUSTOMER'S PURCHASE OF OUR PRODUCTS. IT IS CUSTOMER'S SOLE AND EXCLUSIVE RESPONSIBILITY TO TEST AND ENSURE SUITABILITY OF OUR PRODUCTS FOR ITS CUSTOMERS' OR END-USER'S APPLICATION.

CONTACT INFORMATION

Copyright 2017 Ricoh Electronics, Inc.
1125 Hurricane Shoals Rd.
Lawrenceville, GA 30043
All Rights Reserved

Company Info
ISO14001 / ISO9001 Certified

Customer Service Department
Toll-Free 1-800-843-7058
Toll-Free Fax 1-888-873-7059
Worldwide Fax +1-714-259-4349
Email: orders@rei.ricoh.com