



SPECIFICATION SHEET

This product specification sheet provides the detail to aid you in identifying the most appropriate product type to meet your company's specific requirements. Please direct questions to: **Ricoh Customer Service 1-800-843-7058**

DESCRIPTION

N140LA's direct thermal top coated label stock is durable, has medium sensitivity, strong resistance to plasticizers, and prints at high speeds.

KEY FEATURES

Standard top-coated thermal paper; Medium-high image resolution; Medium sensitivity; Strong image preservation against most environments.

— APPLICATION AREAS —



Weigh Scale Labels



Shipping Labels



Meat Processing



Distribution/Inventory



Product ID

FACESTOCK / PRESERVATION PROPERTIES

FACESTOCK PROPERTIES

ITEM	UNIT	SPECIFICATION	TEST METHOD
Basis Weight	lbs (24x36x500 sheets)	43.6 ± 4.3	TAPPI T-410
	g/m ²	71 ± 7	
Caliper	mil	3.0 ± 0.3	TAPPI T-411
	µm	76 ± 7	
Image Color		Black	Visual Check
Image Density	(ODU) Minimum	1.25	X-Rite Densitometer
Tear Strength	MD gf Minimum	30	TAPPI T-414
	CD gf Minimum	35	
Tensile Strength	MD kgf/15 mm Minimum	5	TAPPI T-494
	CD kgf/15 mm Minimum	2.5	
Stiffness	MD g-cm Minimum	3.0	TAPPI T-489
	CD g-cm Minimum	2.5	


PRESERVATION PROPERTIES

ITEM	SPECIFICATION	TEST METHOD
Oil Resistance	Image	1.10 Minimum
	Background	0.30 Maximum
Moisture Resistance	Image	40° C, Dry, 15 Hours
	Background	X-Rite (ODU)
Heat Resistance	Image	1.10 Minimum
	Background	0.30 Maximum
Light Resistance	Image	80° C, Dry, 1 Hour
	Background	X-Rite (ODU)
Light Resistance	Image	5000 lx, 100 Hours
	Background	X-Rite (ODU)




SENSITIVITY RESULTS

Dynamic Sensitivity



Static Sensitivity



Sensitivity curves are for reference only.

Storage Conditions: Below 95°F (35° C) and less than 85% R.H. in a warehouse, avoiding direct sunlight.

Tests performed on Markpoint MP104.

N140LA – LAMINATED PRODUCT

GRADE	UNIT	G25	G8	G22
Application	°F	-40 to 122	10 to 120	28 to 120
Temperature	°C	-40 to 50	-12 to 49	-2 to 50
Service	°F	-65 to 131	-20 to 120	-40 to 122
Temperature	°C	-54 to 55	-29 to 49	-40 to 50
Basis Weight	lbs	98 ± 12	95 ± 12	101 ± 12
(24 x 36 x 500)	g/m ²	160 ± 19	154 ± 19	164 ± 19
Caliper	µm	152 ± 18	152 ± 18	157 ± 18
	mil	6.0 ± 0.7	6.0 ± 0.7	6.2 ± 0.7

Liner: 40 lbs
 Caliper: 2.5 mils ± 10% (64 ± 8 µm)
 Opacity: 65% Maximum (Photovolt)

Adhesive Attributes:
 G25 – Wide Temperature and Permanent
 G8 – Tight Removable
 G22 – Hot Melt for High Moisture Environments

CERTIFICATES / REGULATIONS / DIRECTIVES

BPA Free No Added PFAS ISO9001 ISO14001 Indirect Food Contact

RICOH ELECTRONICS, INC. DISCLAIMS ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE IN CONNECTION WITH THE CUSTOMER'S PURCHASE OF OUR PRODUCTS. IT IS CUSTOMER'S SOLE AND EXCLUSIVE RESPONSIBILITY TO TEST AND ENSURE SUITABILITY OF OUR PRODUCTS FOR ITS CUSTOMERS' OR END-USER'S APPLICATION.

CONTACT INFORMATION

Copyright 2024 Ricoh Electronics, Inc.
 1125 Hurricane Shoals Rd.
 Lawrenceville, GA 30043
 All Rights Reserved

Company Info
 ISO14001 / ISO9001 Certified

Customer Service Department
 Toll-Free 1-800-843-7058
 Toll-Free Fax 1-888-843-7059
 Worldwide Fax +1-770-613-6478
 Email: orders@rei.ricoh.com