

# B110CR

(For Flat Head Printers)

**RICOH**  
imagine. change.

## Thermal Transfer Ribbon Product Information

### RESIN SUPER SMEARLESS

Last update:  
Sep. 2024  
Ref: PS-1659 (Rev. 3)

#### RIBBON PROPERTY

- Base Material
- Base Thickness ( $\mu\text{m}$ )

Polyester film  
4.5  $\pm$  0.4

#### INK PROPERTY

- Ink Color

Black

#### IMAGE PROPERTY

- Image Density
- Image Resolution
- Scratch Resistance
- Chemical Resistance
- Ethanol, Methanol
- IPA (Isopropyl Alcohol)
- Windshield Washer
- Gasoline, Diesel Fuel, Gasohol
- Engine Oil, Mission Fluid
- Power Steering Fluid
- Brake Fluid
- Engine Coolant

1.5 minimum  
Excellent  
Excellent  
Excellent  
Excellent  
Excellent  
Excellent  
Excellent  
Excellent  
Excellent  
Excellent  
Excellent

*\* All tests specifications are based on Ricoh's standard test results.*

#### USAGE ENVIRONMENT:

5 ~ 35°C (41 ~ 95°F), 30 ~ 85%RH

#### STORAGE CONDITIONS:

Keep indoors, away from high temperatures, high humidity and direct sunlight. Keep master rolls hanging horizontally.

#### GUARANTEE PERIOD:

\*Finished rolls:

4 years after manufacturing

#### FEATURES:

- Ideal for Automotive, Serial No. Plates, Circuit Board Labels and Pharmaceutical Applications
- Produces very high resolution even when printing using a 600dpi thermal head
- Excellent resistance to heat, chemicals, solvents and scratches
- UL recognized with various printers and films

*The above data represents product averages, allowing for industry accepted variances. These products should be tested in the end-use conditions to ensure that they meet the requirements of the specific application. Specifications may change without notice.*

RICOH ELECTRONICS, INC. DISCLAIMS ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE IN CONNECTION WITH THE CUSTOMER'S PURCHASE OF OUR PRODUCTS. IT IS CUSTOMER'S SOLE AND EXCLUSIVE RESPONSIBILITY TO TEST AND ENSURE SUITABILITY OF OUR PRODUCTS FOR ITS CUSTOMERS' OR END-USER'S APPLICATION.