



SPECIFICATION SHEET

This product specification sheet provides the detail to aid you in identifying the most appropriate product type to meet your company's specific requirements.
Please direct questions to: **Ricoh Customer Service 1-800-843-7058**

DESCRIPTION

N140LA BF is a durable direct thermal top coated label stock ideal for high speed printing. It has medium sensitivity and offers strong resistance to plasticizers.

KEY FEATURES

Standard top-coated thermal paper with BPS free formulation; Medium-high image resolution; Strong moisture, plasticizer, and water resistance

— APPLICATION AREAS —



Weigh Scale Labels



Shipping Labels



Meat Processing



Distribution/Inventory



Product ID

FACESTOCK / PRESERVATION PROPERTIES

FACESTOCK PROPERTIES

ITEM		UNIT	SPECIFICATION	TEST METHOD
Basis Weight		lbs (24x36x500 sheets)	43.6 ± 4.9	TAPPI T-410
		g/m2	71 ± 8	
Caliper		mil	3.0 ± 0.3	TAPPI T-411
		µm	76 ± 7	
Image Color			Black	Visual Check
Image Density	(ODU)	Minimum	1.20	X-Rite Densitometer
Tear Strength	MD	gf Minimum	30	TAPPI T-414
	CD	gf Minimum	35	
Tensile Strength	MD	kgf/15 mm Minimum	5.4	TAPPI T-494
	CD	kgf/15 mm Minimum	2.7	
Stiffness	MD	g-cm Minimum	3.0	TAPPI T-489
	CD	g-cm Minimum	2.5	
Initial Activation Temperature	(O.D. = 0.2)	°F / °C	181 / 83	
Effective Activation Temperature	(O.D. = 0.8)	°F / °C	208 / 98	


PRESERVATION PROPERTIES

ITEM		SPECIFICATION	TEST METHOD
Oil Resistance	Image	1.10 Minimum	40° C, Dry, 15 Hours
	Background	0.30 Maximum	X-Rite (ODU)
Moisture Resistance	Image	1.10 Minimum	40° C, 90% RH, 24 Hours
	Background	0.30 Maximum	X-Rite (ODU)
Heat Resistance	Image	1.10 Minimum	80° C, Dry, 1 Hour
	Background	0.30 Maximum	X-Rite (ODU)
Light Resistance	Image	1.10 Minimum	5000 lx, 100 Hours
	Background	0.30 Maximum	X-Rite (ODU)




SENSITIVITY RESULTS

Dynamic Sensitivity



Static Sensitivity



Sensitivity curves are for reference only.
Storage Conditions: Below 95°F (35° C) and less than 85% R.H. in a warehouse, avoiding direct sunlight.
Tests performed on Markpoint MP104.

N140LA BF – LAMINATED PRODUCT

GRADE	UNIT	G25	G8	G22
Application	°F	-40 to 122	10 to 120	28 to 120
Temperature	°C	-40 to 50	-12 to 49	-2 to 50
Service	°F	-65 to 131	-20 to 120	-40 to 122
Temperature	°C	-54 to 55	-29 to 49	-40 to 50
Basis Weight	lbs	98 ± 12	95 ± 12	101 ± 12
(24 x 36 x 500)	g/m ²	160 ± 19	154 ± 19	164 ± 19
Caliper	µm	152 ± 18	152 ± 18	157 ± 18
	mil	6.0 ± 0.7	6.0 ± 0.7	6.2 ± 0.7

Liner: 40 lbs
Caliper: 2.5 mils ± 10% (64 ± 8 µm)
Opacity: 65% Maximum (Photovolt)

Adhesive Attributes:
G25 – Wide Temperature and Permanent
G8 – Tight Removable
G22 – Hot Melt for High Moisture Environments

CERTIFICATES / REGULATIONS / DIRECTIVES

BPA Free BPS Free No Added PFAS ISO9001 ISO14001
Indirect Food Contact

RICOH ELECTRONICS, INC. DISCLAIMS ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE IN CONNECTION WITH THE CUSTOMER'S PURCHASE OF OUR PRODUCTS. IT IS CUSTOMER'S SOLE AND EXCLUSIVE RESPONSIBILITY TO TEST AND ENSURE SUITABILITY OF OUR PRODUCTS FOR ITS CUSTOMERS' OR END-USER'S APPLICATION.

CONTACT INFORMATION

Copyright 2024 Ricoh Electronics, Inc. 1125 Hurricane Shoals Rd. Lawrenceville, GA 30043 All Rights Reserved	Company Info ISO14001 / ISO9001 Certified	Customer Service Department Toll-Free 1-800-843-7058 Toll-Free Fax 1-888-843-7059 Worldwide Fax +1-770-613-6478 Email: orders@rei.ricoh.com
--	---	--